MOTIP Wheel Silver - Limited Edition

Technické informace



Renew and repair steel and other light metal rims and hubcaps of your car with MOTIP Wheel Paint. Wheel Paint is a fast-drying acrylic paint with lasting gloss offering good coverage, excellent adhesion and good surface hardness. It is resistant to petrol, chemicals, the weather and is UV-resistant and non-fading. Wheel Paint is resistant to wear and scratches.

Objednací číslo: 604007

Kvalita & vlastnosti

Non-fading and UV-resistant
Fast drying
Good coverage
Resistant to petrol, chemicals and weather influences
Good surface hardness
Lasting gloss
Wear-resistant and scratch free
Excellent adhesion

Fyzikální & chemické údaje

Základní nátěr: Acrylic resin
Název barvy: silver
Stupeň lesku: gloss, >75
Vydatnost: 600 ML – 4 - 5
Vyschnutí pro prach: 5 - 10 min
Vyschnutí na dotek: 10 - 20 min
Úplné vyschnutí: 120 min
Přetíratelné: 120 min
Povrchy: Steel and light metal rims and hubcaps
Minimální provozní teplota: 10 °C
Maximální provozní teplota: 25 °C
Bod vzplanutí: n.a.
Obsah: 600 ML

Jak používat

Before use, carefully read the directions on the packaging and act accordingly.
Pre Treatment: The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of MOTIP primer suitable for the surface. After drying, sand the base layer (grain 600).
Treatment: The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C.
Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.
In order to obtain high gloss, apply a finishing coat of MOTIP acrylic clear coat.
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Šetrné k životnímu prostředí

Společnost European Aerosols se snaží používat přípravky bez zakázaných nebo kritických složek a dosahovat co nejlepších výsledků. Víčka a obaly jsou vyrobeny z recyklovatelného materiálu.

Likvidace

Do recyklačního kontejneru nebo do příslušného kontejneru na využitelný odpad byste měli vyhazovat pouze zcela prázdné plechovky. Nevyprázdněné plechovky by se měly likvidovat jako "zvláštní odpad".

Označení/štítky

Všechny výrobky společnosti European Aerosols splňují aktuální předpisy pro značení podle směrnice opřípravcích 1999/45/ES. Všechny aerosoly odpovídají směrnicím TRGS 200 a TRG 300 a také směrnici 75/324/EHS o aerosolech v aktuálně platném znění.

Ke dni Ožujak 24, 2026 – Tato verze nahrazuje všechny případné předchozí verze.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com